

INCLINED TUBE MANOMETER



Model summary

Model code	Pressure range	Accuracy	Gauge fluid
MM±50 *)	-50... 0 ... +50 Pa	1 Pa	Red
MM100 *)	-20... 0 ... +100 Pa	1 Pa	Red
MM±100	-100... 0 ... +500 Pa	5 Pa/25 Pa	Red
MM200600	0... 600 Pa	5 Pa/25 Pa	Red
MM5001500	0... 1500 Pa	10 Pa/50 Pa	Blue

*) The types are delivered with level bubble

Accessories

Standard accessories:

- 2 fixing screws
- Gauge fluid
- 2 m tube \varnothing 4 / 7 mm
- Red and green pressure limit stickers (e.g. filter clean / filter dirty)

Optional accessories:

- Plastic duct connectors
- Metallic duct connectors

Technical data

Materials	Housing Cover Screws Sealing	ABS PMMA PC NBR
Weight	420 grams	
Ambient conditions	Operation	-40...+60°C
Max. Pressure	200 kPa (2 bar)	
Gauge fluid	Red, s.g. 0,786 kg/dm ³ (15 °C) Blue, s.g. 1,870 kg/dm ³ (15 °C)	
Safety	The structure of the manometer has a special feature that prevents gauge fluid exit during over pressure situation.	

Mounting position Vertical

Dimensions

