

Szivárgóáram-mérő lakatfogók

2412



2413F



2417



2431



2432



2433/2433R



2434



Vezeték mérete	φ 40mm	φ 68mm	φ 40mm	φ 24mm	φ 40mm	φ 40mm	φ 28mm
ACA	20/200mA/ 2/20/200/500A	200mA/ 2/20/200/1000A	200/2000mA/ 20/200/500A	20/200mA/200A	4/40mA/100A	40/400mA/400A	400mA/4/100A
ACV	600V						
Ω	200Ω						
A külső biztonsági mágneses tér hatása φ 15mm 100A	10mA AC max.	10mA AC max.	10mA AC max.	10mA AC max.	2mA AC max.	10mA AC max.	20mA AC max.
Frekvenciaválasztó kapcsoló	•	•	•	•	•	•	•
Adat tartása	•	•	•	•	•	•	•
Csúcstartás		•			•	•	
Auto kikapcsolás	•		•	•	•	•	•
Analóg kimenet	DC 200mV	AC/DC 200mV					
Frekvencia- menet	40~400Hz	40Hz~1kHz	40~400Hz	40~400Hz	20Hz~1kHz 40Hz~1kHz 100A)	20Hz~1kHz 40Hz~1kHz 400A)	40~400Hz
valódi RMS			•			• (2433R)	
Vonatkozó szabványok		IEC61010-1 CAT. III 300V IEC61010-2-032	IEC61010-1 CAT. III 300V IEC61010-2-032	IEC61010-1 CAT. III 300V IEC61010-2-032	IEC61010-1 CAT. III 300V IEC61010-2-032	IEC61010-1 CAT. III 300V IEC61010-2-032	IEC61010-1 CAT. III 300V IEC61010-2-032
Áramforrás	6F22×1 or AC Adaptor	6F22×1	6F22×1	LR44×2	R03×2	R03×2	R03×2
Elem élettartam	100h	35h	50h	15h	40h	40h (2433) 24h (2433R)	150h
Méret (L) × (W) × (D)	209×96×45	250×130×50	209×96×45	149×60×26	185×81×32	185×81×32	169×75×40
Tömeg (kb.)	450g	570g	450g	120g	290g	270g	110g